



MEDIDAS según ASME B16.9

| Dimensiones en mm | | | | | Peso |
|-------------------|-----|-------|------|-------|--------|
| Pulg. | SCH | D | t | B | Kg/pc. |
| 1/2" | 10s | 21,30 | 2,11 | 25,40 | 0,070 |
| | 40s | 21,30 | 2,77 | 25,40 | 0,090 |
| | 80s | 21,30 | 3,73 | 25,40 | 0,140 |
| | 160 | 21,30 | 4,78 | 25,40 | 0,150 |
| 3/4" | 10s | 26,70 | 2,11 | 28,60 | 0,090 |
| | 40s | 26,70 | 2,87 | 28,60 | 0,120 |
| | 80s | 26,70 | 3,91 | 28,60 | 0,200 |
| | 160 | 26,70 | 5,56 | 28,60 | 0,300 |
| 1 | 10s | 33,40 | 2,77 | 38,10 | 0,200 |
| | 40s | 33,40 | 3,38 | 38,10 | 0,250 |
| | 80s | 33,40 | 4,55 | 38,10 | 0,390 |
| | 160 | 33,40 | 6,35 | 38,10 | 0,470 |
| 1 1/4 | 10s | 42,20 | 2,77 | 47,60 | 0,330 |
| | 40s | 42,20 | 3,56 | 47,60 | 0,420 |
| | 80s | 42,20 | 4,85 | 47,60 | 0,550 |
| | 160 | 42,20 | 6,35 | 47,60 | 0,890 |
| 1 1/2 | 10s | 48,30 | 2,77 | 57,20 | 0,460 |
| | 40s | 48,30 | 3,68 | 57,20 | 0,600 |
| | 80s | 48,30 | 5,08 | 57,20 | 1,020 |
| | 160 | 48,30 | 7,14 | 57,20 | 1,430 |

| Dimensiones en mm | | | | | Peso |
|-------------------|-------|--------|--------|--------|--------|
| Pulg. | SCH | D | t | B | Kg/pc. |
| 2 | 10s | 60,30 | 2,77 | 63,50 | 0,630 |
| | 40s | 60,30 | 3,91 | 63,50 | 0,870 |
| | 80s | 60,30 | 5,54 | 63,50 | 1,590 |
| | 160 | 60,30 | 8,74 | 63,50 | 3,180 |
| 2 1/2 | 10s | 73,00 | 3,05 | 76,20 | 1,100 |
| | 40s | 73,00 | 5,16 | 76,20 | 1,700 |
| | 160 | 73,00 | 9,52 | 76,20 | 3,630 |
| | 10s | 88,90 | 3,05 | 85,70 | 1,370 |
| 3 | 40s | 88,90 | 5,49 | 85,70 | 1,900 |
| | 80s | 88,90 | 7,62 | 85,70 | 4,450 |
| | 160 | 88,90 | 11,13 | 85,70 | 5,870 |
| | 3 1/2 | 10s | 101,60 | 3,05 | 95,30 |
| 40s | | 101,60 | 5,74 | 95,30 | 3,190 |
| 10s | | 114,30 | 3,05 | 104,80 | 2,150 |
| 4 | | 40s | 114,30 | 6,02 | 104,80 |
| | 80s | 114,30 | 8,56 | 104,80 | 7,710 |
| | 160 | 114,30 | 13,49 | 104,80 | 9,760 |
| | 5 | 10s | 141,30 | 3,40 | 123,80 |
| 40s | | 141,30 | 6,55 | 123,80 | 6,550 |
| 80s | | 141,30 | 9,53 | 123,80 | 11,340 |

| Dimensiones en mm | | | | | Peso |
|-------------------|-----|--------|-------|--------|--------|
| Pulg. | SCH | D | t | B | Kg/pc. |
| 6 | 10s | 168,30 | 3,40 | 142,90 | 4,76 |
| | 40s | 168,30 | 7,11 | 142,90 | 9,73 |
| | 80s | 168,30 | 10,92 | 142,90 | 13,60 |
| 8 | 10s | 219,10 | 3,76 | 177,80 | 8,40 |
| | 40s | 219,10 | 8,18 | 177,80 | 18,00 |
| 10 | 10s | 273,10 | 4,19 | 215,90 | 14,20 |
| | 40s | 273,10 | 9,27 | 215,90 | 30,80 |
| 12 | 10s | 323,90 | 4,57 | 254,00 | 21,60 |
| | 40s | 323,90 | 9,53 | 254,00 | 44,30 |
| 14 | 10s | 355,60 | 4,78 | 279,40 | 48,53 |
| | STD | 355,60 | 9,53 | 279,40 | 79,38 |
| 16 | 10s | 406,40 | 4,78 | 304,80 | 58,97 |
| | STD | 406,40 | 9,53 | 304,80 | 99,79 |
| 18 | 10s | 457,20 | 4,78 | 342,90 | 76,66 |
| 20 | 10s | 508,00 | 5,54 | 381,00 | 103,42 |
| 24 | 10s | 609,60 | 6,35 | 431,80 | 155,58 |

NORMAS SEGUN MATERIAL

| MATERIAL | NORMA ASTM |
|-----------------------------|------------|
| DUPLEX S31803 / 1.4462 | A815 |
| SUPERDUPLEX S32750 / 1.4410 | A815 |
| SUPERDUPLEX S32760 / 1.4501 | A815 |
| 904L N08904 / 1.4539 | B366 |
| 254SMo S31254 / 1.4547 | A403 |
| HASTELLOY C22 / C276 | B366 |
| INCOLOY 800HT / 825 | B366 |
| MONEL 400 / K500 | B366 |
| INCONEL 600 / 601 / 625 | B366 |

OTROS PRODUCTOS DISPONIBLES



BARRA MACIZA
Diam. 10 a 400 mm



TUBERÍA SIN SOLDADURA
1/2" A 8" SCH10 A SCH80S



TUBERÍA SOLDADA
Diam. 10 a 400 mm



BRIDAS DIN / ASA
1/2" A 24" 150lbs - 3000lbs



CHAPA
Esp. 0.5 a 40 mm



CODOS, TES, REDUCC...
BW, SW, ALTA PRESIÓN...
D8" A 24" SCH10 A SCH80S